



FW= Frame width
 Min. 1800 / max. 3000
 Alt. F FW=2COW+35+X
 Alt. U FW=2COW+31+X

FH= Frame height
 Min. 1950 / max. 3000

X= Distance to avoid finger trap
 (25 mm)

COW= Clear opening width
 Alt. F COW=(FW-35-X)/2
 Alt. U COW=(FW-35-X)/2+2

COH= Clear opening height
 COH=FH-50

CL= Cover length

State when ordering
 FW=.....mm
 FH=.....mm
 X=.....mm
 COW=.....mm
 COH=.....mm
 Cover
 CL=.....mm

Profile option
 Alt. F (concrete/brick)
 Alt. U (aluminium/steel)

Surface treatment
 Silver anodized
 Special anodized.....
 RAL.....
 Special powder coating.....

Glass
 8 mm laminated glass
 10 mm laminated glass
 12 mm laminated glass
 8 mm tempered glass
 10 mm tempered glass

Lock
 Floor lock Euro 1-way
 Floor lock Euro 2-way

Scale 1:5

Customer: _____
 Door id: _____
 Project No: _____

EntreMatic ref: _____
 Date: _____
 Sign: _____

Profile system
EMPS with EMSL
2 Panel wall mounted opening left

ENTRE MATIC

2 832997