



**State when ordering**  
 FW=.....mm  
 FH=.....mm  
 X=.....mm  
 COW=.....mm  
 COH=.....mm  
 Cover  
 CL=.....mm

**Profile option**  
 Alt. F (concrete/brick)  
 Alt. U (aluminium/steel)

**Surface treatment**  
 Silver anodized  
 Special anodized.....  
 RAL.....  
 Special powder coating.....  
 .....

**Glass**  
 8 mm laminated glass  
 10 mm laminated glass  
 12 mm laminated glass  
 8 mm tempered glass  
 10 mm tempered glass

**Lock**  
 Floor lock Euro 1-way  
 Floor lock Euro 2-way

FW= Frame width  
 Min. 1600 / max. 4800  
 Alt. F FW=3COW/2+33,5+X  
 Alt. U FW=1,5COW+30,5+X

FH= Frame height  
 Min. 1950 / max. 3000

X= Safety distance (50 mm)

COW= Clear opening width  
 Alt. F COW=2(FW-33,5-X)/3  
 Alt. U COW=2(FW-33,5-X)/3+2

COH= Clear opening height  
 COH=FH-50

CL= Cover length

Scale 1:5

Customer: \_\_\_\_\_

Door id: \_\_\_\_\_

Project No: \_\_\_\_\_

EntreMatic ref: \_\_\_\_\_

Date: \_\_\_\_\_

Sign: \_\_\_\_\_

**Profile system**  
**EMPS-T with EMSL-T**  
**3 Panel wall mounted left**

**ENTRE MATIC**

2 833061